

SILICONE FG40R

Silicone cables

Multi core cable with silicone rubber insulation and PVC sheath.



TECHNICAL DATA

Nominal tension	300/500 V
Type of electrical conductor	Flexible red copper
Type of insulation	EI2 (EN 50363-1)
Type of outer sheath	TM3 (EN 50363-4-1)
Color of the outer sheath	Black
Operating temperature	-60° C +90° C
Test voltage	2000 V

REFERENCES STANDARDS

Conductor	EN 60228; IEC 60228
-----------	---------------------

DIMENSIONS

Nominal section	Wires max diameter	Conductor diameter	Insulation thickness	Diametro isolamento $\pm 0,1$	Minimum average external diameter	Medium outer diameter $\pm 0,2$	Electrical resistance 20°C	Approximate weight	Fattore CU
(Nxmm ²)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(?/km)	(kg/km)	(kg/km)
2x0,50	0,21	0,86	0,60	N/A	0,60	5,6	39,0000	N/A	9,6000
2x0,75	0,21	1,05	0,60	N/A	0,60	6,0	26,0000	N/A	14,4000
2x1,00	0,21	1,21	0,60	N/A	0,80	6,6	19,5000	N/A	19,2000
2x1,50	0,26	1,49	0,70	N/A	0,80	7,6	13,3000	N/A	28,8000
3x0,50	0,21	0,86	0,60	N/A	0,60	5,9	39,0000	N/A	14,4000
3x0,75	0,21	1,05	0,60	N/A	0,60	6,3	26,0000	N/A	21,6000
3x1,00	0,21	1,21	0,60	N/A	0,80	7,0	19,5000	N/A	28,8000
3x1,50	0,26	1,49	0,70	N/A	0,90	8,2	13,3000	N/A	43,2000
4x0,75	0,21	1,05	0,60	N/A	0,80	7,3	26,0000	N/A	28,8000
4x1,00	0,21	1,21	0,60	N/A	0,90	7,8	19,5000	N/A	38,4000
5x0,75	0,21	1,05	0,60	N/A	0,90	8,2	26,0000	N/A	36,0000
5x1,00	0,21	1,21	0,60	N/A	0,90	8,5	19,5000	N/A	48,0000

CORES IDENTIFICATION

Cores number	Insulation colour sequence
2	NA
3	NA
4	NA
5	NA

Refer to the CEI EN 50565 standard series as a guide to the use of cables with nominal voltage not exceeding 450/750 V (U0/U) and to the CEI 20-92 standard as a guide for the handling and storage of wooden reels for cables electrical.

Elettro Brescia S.p.A. - Via Bulloni 36 - 25050 - Camignone di Passirano (Bs) - Tel, +39 030 6850663 Fax +39 030 6850444 email: info@elettrobrescia.it